

“SLASHBUSTER”[®]

LW 362M

Excavator Mounted Stirring Attachment



“SLASHBUSTER”

State-of-the-Art

**Land Management and
Right-of-Way Equipment**

"SLASHBUSTER"®

LW 362M

Excavator Mounted Stirring Attachment

LW 362M

General Specifications

Adaptable to 2-50 ton excavators
48" stirring depth (standard model)
Sealed bearing assembly
Self-purging grease system
Continuous underwater operation
Quick change mounting pins
Boom geometry not modified
Automatic wire shear standard
Rotating hub debris guard standard
Adjustable RPM

Basic Installation Requirements

Motor Circuit:

Continuous service priority flow required
Flow to 60 GPM
Pressure to 3850 PSI
Three position directional control valve recommended
Adjustable flow available
Forward, neutral and reverse rotation
"SLASHBUSTER"® attachments are provided with
crossport relief and anti-cavitation protection

Recommended Electric:

20 Amp auxiliary circuit recommended
Foot-operated master on/off switch recommended
Cab-mounted control for forward, neutral and
reverse with indicator light recommended



Note: It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.

- **INCREASE PRODUCTION** with a continuous stirring action
- **INCREASE PROFITS** low maintenance and low initial cost
- **EASY TO OPERATE** helps prevent damage to cell lining
- **LASER DEPTH CONTROL** option to aid in performance
- **VERSATILE** adaptable to any excavator
- **STRONG** not affected by lumber or plastic in slurry

"SLASHBUSTER"®
EQUIPMENT

Unmatched in Performance,
Reliability and Output



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563
(360) 249-3366

email: info@slashbuster.com
www.slashbuster.com

Exclusive Manufacturer of "SLASHBUSTER"® Equipment

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.