

"SLASHBUSTER"®

XL 330

Mini Excavator Brush Cutting Attachment

XL 330

General Specifications

Adaptable to 2-5 ton excavators
Cuts and mulches brush to 1.5" diameter
33" cutting swath with blade bar
200-300 pounds total weight

Options:

Integration with bucket quick disconnects
Remote herbicide applicator

Basic Installation Requirements

Motor Circuit:

Excavator auxiliary circuit
8 GPM to 15 GPM flow
2,500 PSI minimum recommended
"SLASHBUSTER"® attachments
are provided with crossport relief
and anti-cavitation protection

Recommended Electric:

As needed

Note: It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.

"SLASHBUSTER"®
EQUIPMENT

Unmatched in Performance,
Reliability and Output



33" Blade Bar Cutter



100%
triple
welded
construction



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563
(360) 249-3366

email: info@slashbuster.com
www.slashbuster.com

Exclusive Manufacturer of "SLASHBUSTER"® Equipment

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.