

"SLASHBUSTER"®

XL 460D

Brush Cutting Attachment for Smaller Excavators

XL 460D

General Specifications

- Adaptable to 5-12 ton excavators
- Cuts and mulches brush to 6" diameter
- Mulching disk with replaceable carbide teeth
- 44" cutting swath
- 700-850 pounds total weight
- Automatic wire shear standard
- Rotating hub debris guard standard
- Brush rake standard

Options:

- 90 degree tilt mount
- Remote herbicide applicator
- Integration with bucket quick disconnects
- Integration with standard excavator bucket thumb

Basic Installation Requirements

Motor Circuit:

- Excavator auxiliary circuit
- 16 GPM to 22 GPM flow
- 3,000-3500 maximum PSI

"SLASHBUSTER"® attachments are provided with crossport relief and anti-cavitation protection

Recommended Electric:

As needed

Note: It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.



Mulching Disk



Brush Rake

SLASHBUSTER.com

LAND MANAGEMENT EQUIPMENT

Unmatched in Performance,
Reliability and Output



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563
(360) 249-3366

email: info@slashbuster.com
www.slashbuster.com

Exclusive Manufacturer of "SLASHBUSTER"® Equipment

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.