

"SLASHBUSTER"®

HD 482 & HD 422

Excavator Mounted Brush Cutting Attachment

MAGNUM
STANDARD DRIVE SYSTEM

**Recommended for
Long Front or
Standard Front
Excavators**

**"SLASHBUSTER"
State-of-the-Art
Land Management and
Right-of-Way Equipment**

*It's Not How Fast You Cut,
It's How Well You Cut Fast*

*Exclusive Worldwide Patents
The Most Versatile Cutter Available*

Applications of the D&M "SLASHBUSTER"® Equipment

1. Building roads over swampy ground
2. Clearing and grubbing contracts
3. Clearing building sites
4. Eliminates slash disposal burning in populated areas
5. Cuts costs of trucking debris from cleared areas.
All cuttings are mulched into soil.
6. Builds new and maintains established right-of-ways.
7. Retards tall growing trees eliminating blanket spray programs
8. Daylighting roads cutting the expense of sanding
9. Sight obstructions removed from corners and intersections.
10. Better maintenance of drainage ditches.
11. Brush clearing around bridges gives greater exposure to sunlight with easier and more economical maintenance, especially with older structures.



Mulching Teeth in Shroud



"SLASHBUSTER"®

HD 482 & HD 422

Excavator Mounted Brush Cutting Attachment

HD 482

General Specifications

- 52" cutting swath
- Cuts and mulches trees to 18" diameter
- Adaptable to 40,000 to 100,000-lb excavators
- Adjustable 350 to 550 RPM wheel speed
- 2,900 to 3,900 pounds total weight*

HD 422

General Specifications

- 46" cutting swath
- Cuts and mulches trees to 14" diameter
- Adaptable to 24,000 to 60,000-lb excavators
- Adjustable 350 to 550 RPM wheel speed
- 2,400 to 2,900 pounds total weight*

Basic Installation Requirements for Both Models

Hydraulic:

- Dual pump continuous service priority flow required
- Adjustable flow of 32 GPM to 40 GPM*
- 4,000 PSI maximum pressure
- Case drain line direct to reservoir, unobstructed
- "SLASHBUSTER"® attachments are provided with crossport relief and anti-cavitation protection

Recommended Electric:

- 20 AMP auxiliary circuit
- Foot-operated master on/off switch
- Cab mounted control for forward, neutral and reverse* with indicator light

*Varies with excavator size and options

Note: It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.

HD 482 & HD 422 Standard Features:

- MAGNUM drive system
- Automatic wire shear
- Rotating hub debris guard
- Cutting disk with S-7 cast and hardened teeth
- Mulching teeth in shroud

HD 482 & HD 422 Options:

- Available to operate with standard bucket thumb
- Available to match any bucket quick disconnect
- Ninety-degree tilt mount



"SLASHBUSTER"®

EQUIPMENT

Unmatched in Performance,
Reliability and Output



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563
(360) 249-3366

email: info@slashbuster.com
www.slashbuster.com

Exclusive Manufacturer of "SLASHBUSTER"® Equipment

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.