"SLASHBUSTER" SG 240 Stump Grinder Backhoe · Tractor · Loader · Excavator Mounted Attachment



State-of-the-Art **Land Management and Right-of-Way Equipment**







Mounts on any backhoe with at least 80 horsepower

SLASHBUSTER®

Backhoe Mounted Stump Grinder Attachment

SG 240

General Specifications

Adaptable to 10-16 ton excavators or Backhoe • Tractor • Loader with 80 HP minimum Carbide Teeth

Enclosed shroud for safer operation Patented guide cones prevent wheel stalls Integrated heel rack for digging / pushing / pulling **Options:**

Tilt Mount - tilts 45 degrees either side of center

Basic Installation Requirements

Motor Circuit:

Dual pump continuous service priority flow required 44 GPM maximum flow

3,000 PSI maximum pressure


"SLASHBUSTER"® attachments are provided with crossport relief and anti-cavitation protection

Recommended Electric:

20 AMP auxiliary circuit recommended Foot-operated master on/off switch recommended



Patented Guide Cones for smooth, easy operation



Unique 3-Position Carbide Teeth easy to change and rotate

SLASHBUSTER®

EQUIPMENT

Unmatched in Performance, Reliability and Output



12 Monte-Brady Road Montesano, WA 98563 (360) 249-3366



Use the **Double Heel Rack** to remove obstructions and dig around the stump when grinding below soil level

OPTIONAL TILT MOUNT tilts 45 degrees either side of center