

# "SLASHBUSTER"®

## XL 480B

Brush Cutting Attachment with Patented Third Boom

### XL 480B

#### General Specifications

- 48" cutting swath
- Cuts and mulches brush and trees to 10" diameter
- Adaptable to 20,000 to 40,000-lb standard front excavators
- Standard integrated material handler
- Standard automatic wire shear
- Standard rotating hub debris guard
- Standard "SLASHBUSTER"® cutting disk with S-7 teeth
- 2,800-lb. to 3,300-lb. total weight

#### Options:

- Blade bar cutting assembly
- Ninety-degree tilt mount



#### Basic Installation Requirements

##### Hydraulic:

- Continuous service priority flow circuit
- 18 - 24 GPM\*
- 4,500 PSI maximum\*
- Case drain line direct to reservoir, unobstructed
- Dual acting cylinder circuit with 15 GPM, 2500 PSI for thumb

##### Recommended Electric:

- 20 AMP auxiliary circuit
- Foot-operated master on/off switch
- Cab mounted control for forward, neutral and reverse\* with indicator light



\*Varies with excavator size and options, per cutter S/N

**Note:** It is recommended that the excavator is provided with a hinged front screen guard for the front of the cab that meets or exceeds SAE J1084 specs.

## "SLASHBUSTER"®

Unmatched in Performance,  
Reliability and Output.



D&M Machine Division, Inc.

12 Monte-Brady Road Montesano, WA 98563  
(360) 249-3366  
email: info@slashbuster.com  
www.slashbuster.com

Exclusive Manufacturer of "SLASHBUSTER"® Equipment

THIS EQUIPMENT IS PROTECTED BY ONE OR MORE OF THE FOLLOWING PATENTS: 4,769,977; 5,103,882; 5,201,350; 5,329,752; 5,408,814; S/N 08/720,536; AUSTRALIAN PATENTS: 600716; 618679; 652131; 654411; 665724; CANADIAN PATENTS: 1,281,908; 2,084,971; NEW ZEALAND PATENTS: 245249; 270419; EUROPEAN PATENT 0298977, REGISTERED IN GB, FR, IT, CH, NL, BE (298977E), DE (37793098), AT (0076250E), SE (879019487); AND PATENTS PENDING IN THE UNITED STATES, AUSTRALIA, CANADA, EUROPE, FINLAND AND NEW ZEALAND.